CAR AND DRIVER TRACK SHEET

PLEASE RETURN TO: TECHNICAL DEPARTMENT
1585 EISENHOWER PLACE, ANN ARBOR, MI 48108

DATE 5/31/2019 **TRACK** CA City, CA **DRIVER** TQ

MAKE/MODEL (W/ALL BADGING) COMPARO LONGTERM INITIAL/FINAL **TURNSLCK-LCK** 2.5
Jaguar XE SV

MODEL YEAR 2019 **ODOMETER** _____ **VIN** SAJAP4FE6KS487659

VEHICLE TYPE FRONT/MID/REAR-*ENGINE* FRONT/REAR/4-*WHEEL-DRIVE* 4 -PASSENGER 4 -DOOR

ENGINE 5.0 -LITER V-8 TURBOCHARGED SUPERCHARGED +MOTOR DIESEL

REDLINE 6800 SHIFTRPM 6200-6500 REVCUT 6800 FUEL 91

TRANS 8 -SPEED MAN/AUTO/CVT AUTOMAN DUALCLUTCH MANUALSHIFTMODE

MSA POWER: WINDOWS/LOCKS/SEATS(DRIVER/PASS) SUNROOF A/C REMOTE(LOCK/START)
PROXYKEY CRUISE REAR(DEFROST/WIPER) [(POWER)TILT/TELE] STEERING WHEEL

STEREO: BRAND Meridian Surround AM/FM/SAT AUX/USB/RCA/BT/MEDIACARD-AUDIO INPUTS
CD(PLAYER/CHANGER) IPOD CONNECTOR _____ -GB MEDIA STORAGE _____ SPEAKERS

TIRES Michelin Pilot Sport Cup 2 PRESS (F/R) 34 / 34
SIZE, FRONT 265/35R20 EXTRA LOAD (T) (99Y) REAR 305/30ZR20 (103Y) EXTRA LOAD (J)
SPARE: COMPACT(HIGH-PRESS/INFLATABLE) FULL USE/SIZE(STEEL/ALUM/MATCH ALUM) INFLATION KIT

STABILITY CONTROL FULLYDEFEAT PARTDEFEAT TRACOFF COMPMODE LAUNCHCTRL

CURB WEIGHT

LF 1100 RF 1077
LR 956 RR 956
TOTAL 4085
%(F/R) 53.2 / 46.8
GVWR 4740 CoG _____

VMAX

DIR	SPEED	GEAR

_____ MPH D G R

SOUND LEVEL

IDLE	51.0 / 51.3	51
WOT	85.8 / 85.5	86
70 CR	69.8 / 70.0	70

TRUE 70MPH 72 INDICATED

PRACTICAL STOWAGE

BOX: ALL UP _____ 3RD DOWN _____
ALL DOWN _____
PIPE _____ FT _____ IN
PLYWOOD _____ IN _____ IN

ONEODOMI = 5230 FT

LATERAL ACCELERATION

300 FT DIA SKIDPAD

LEFT	RIGHT
1.076	1.031

1.05 G
INHIBITED
UNDERSTEER MILD MOD EXCE

SLALOM

TIME	CONES

_____ MPH
INHIBITED

BRAKING

151
152
148
148
147
149

70-0 148
FIRST 151
LONG 151
FADE
(NONE) SLIGHT
MOD HEAVY

ACCELERATION

30	1.5	5-60	3.8
40	2.0	30-50	2.1
50	2.7	50-70	2.7
60	3.5	¼ MILE	
70	4.5	11.8 @ 121	
80	5.6		
90	6.7		
100	8.1		
110	9.7		
120	11.7		
130	14.0		
140	16.7		
150	20.1		
160	25.5		
170	—		

WEATHER

WB 53.4
DB 83.6
INHG 27.30
VP 0.117325
RH 10.1%

CORRECTION

(FULL) HALF
SP 1.01 67
ET 0.9842
LIN 0.9484

NOTES Rec to 7500 no prama

OD Stg Lmr