CAR AND DRIVER TRACK SHEET

PLEASE RETURN TO: TECHNICAL DEPARTMENT
1585 EISENHOWER PLACE, ANN ARBOR, MI 48108

Shell V-Power NITRO+ Premium Gasoline

DATE 08/15/19 TRACK CPG DRIVER MM

MAKE/MODEL (W/ALL BADGING) COMPARO LONGTERM INITIAL/FINAL TURNSLCK-LCK 2.8
Land Rover Range Rover Sport HST P400

MODEL YEAR 2019 ODOMETER 1912 VIN SALWS25V9KA858668

VEHICLE TYPE FRONT/MID/REAR-ENGINE FRONT/REAR/4-WHEEL-DRIVE 5-PASSENGER 4-DOOR

ENGINE 3.0-LITER Inline-6 TURBOCHARGED SUPERCHARGED-MOTOR DIESEL

REDLINE 6900 SHIFTRPM _____ REVCUT _____ FUEL Premium (91)

TRANS 8-SPEED MAN/AUTO/CVT AUTOMAN DUALCLUTCH MANUALSHIFTMODE

MSA POWER: WINDOWS/LOCKS/SEATS DRIVER/PASS SUNROOF A/C REMOTE LOCK/START
PROXYKEY CRUISE REAR(DEFROST/WIPER) (POWER TILT/TELE STEERING WHEEL

STEREO: BRAND Meridian AM/FM/SAT AUX/USB/RCA/BT/MEDIACARD-AUDIO INPUTS
~~CD PLAYER/CHANGER~~ ~~IPODCONNECTOR~~ _____-GB MEDIA STORAGE 23 SPEAKERS

TIRES Continental Cross Contact LX Sport PRESS (F/R) 37 / 44

SIZE, FRONT 275/40R22 108Y M+S Extra Load REAR Same

SPARE: COMPACT/HIGH-PRESS/INFLATABLE FULL USE/SIZE STEEL/ALUM/MATCH ALUM INFLATION KIT

STABILITY CONTROL FULLYDEFEAT PARTDEFEAT TRACOFF COMPMODE LAUNCHCTRL

CURB WEIGHT

LF	1317	RF	1378
LR	1385	RR	1304

TOTAL 5384

%F/R 50.1 / 49.9

GVWR 6724 CoG _____

VMAX

DIR	SPEED	GEAR

_____ MPH D G R

SOUND LEVEL

IDLE	40.6	43.2	42
WOT	75.1	75.3	75
70 CR	68.1	68.4	68

TRUE 70MPH 71 INDICATED

PRACTICAL STOWAGE

BOX: ALL UP _____ 3RD DOWN _____

ALL DOWN _____

PIPE _____ FT _____ IN

PLYWOOD _____ IN _____ IN

ONEODOMI = 5245 FT

LATERAL ACCELERATION

300 FT DIA SKIDPAD

LEFT	RIGHT
15.17	14.94

0.81 G

INHIBITED

UNDERSTEER MILD MOD EXCE

SLALOM

TIME	CONES

_____ MPH

INHIBITED

BRAKING

161
163
163
167
163
163

70-0 163

FIRST 161

LONG 167

FADE
(NONE) SLIGHT
MOD HEAVY

ACCELERATION

30	2.1	5-60	6.9
40	3.1	30-50	4.0
50	4.5	50-70	4.2
60	6.0		
70	7.6		
80	9.7		
90	11.9		
100	15.1		
110	18.7		
120	23.0		
130	31.9		
140			
150			
160			
170			

¼ MILE
14.5 @ 98

WEATHER

WB 72
DB 74
INHG 28.90
VP 0.77165
RH 91.05

CORRECTION

FULL (HWY)
SP 1.0108
ET 0.9899
LIN 0.9574

NOTES